

08-10-00

H

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Box Patent Application
 Assistant Commissioner for Patents
 Washington, D.C. 20231

Date: August 9, 2000

Atty. Docket No. SAA-34-2

Sir:

Transmitted herewith for filing is the continuation-in-part patent application of:

Inventor: Rainer H. Wischinski, has made an invention pertaining to:

For: A METHOD AND APPARATUS FOR PROGRAMMING AN AUTOMATION DEVICE

Enclosed are:

X 7 pages specification, 4 pages of claims, 1 page of Abstract and 2 sets of 3 sheets of informal drawings (Figures 1-4).

X An executed Assignment of the invention to the Schneider Automation Inc.

X An executed Declaration combined with Power of Attorney.

FEE CALCULATION

	Claims Filed / Extra	Rate	Basic Fee 37 CFR 1.16(a) \$ 690.00
Total Claims(37 CFR 1.16(a))	4 - 20 = 3 x	\$18.00	\$ 54.00
Independent Claims	1 - 3 = 1 x	\$78.00	\$ 78.00
TOTAL FILING FEE			\$ 822.00

08/09/00
 JC853 U.S. PTO

JC857 U.S. PTO
 09/635280
 08/09/00


006030 0325960

X Please charge my Deposit Account No. 19-3875 (SAA-34-2).

X \$ 822.00 to cover the total filing fee of \$ 822.00.

X Any additional fees which may be required. Please credit any overpayment to Account No. 19-3875 (SAA-34-2).

Respectfully submitted,



Michael J. Femal

Reg. No. 27,784

Attorney for Applicants

Square D Company
1415 South Roselle Road
Palatine, IL 60067

006030" 0825E360

INVENTOR INFORMATION

Inventor One Given Name:: Rainer H
Family Name:: Wischinski
Postal Address Line One:: Street 110 North Road
City:: Sandown
State or Province:: NH
Country:: USA
Postal or Zip Code:: 03873
Citizenship Country:: Germany

CORRESPONDENCE INFORMATION

Correspondence Customer Number:: 23569
Electronic Mail One:: trechelk@squared.com

APPLICATION INFORMATION

Title Line One:: A METHOD AND APPARATUS FOR PROGRAMMING A
Title Line Two:: N AUTOMATION DEVICE
Total Drawing Sheets:: 3
Formal Drawings?:: No
Application Type:: Utility
Docket Number:: SAA-34-2
Secrecy Order in Parent Appl.?:: No

Source:: PrintEFS Version 1.0.1

005080"03236950

**A METHOD AND APPARATUS FOR
PROGRAMMING AN AUTOMATION DEVICE**

DESCRIPTION

Technical Field

The present invention relates to a control system. More specifically, the present invention relates to a control system on a network having an automation device wherein the operating program for controlling the automation device is to selected from a network device in response to the automation device.

Related Applications

This application is a continuation-in-part of U.S. Patent Application No. ___/___,___ (SAA-34-1) yet to be assigned which is a continuation-in-part of U.S. Patent No. 6,061,603 which is a continuation-in-part of U.S. Patent Application No.09/303,458, which is a continuation-in-part of U.S. Patent Application No.08/927,005. This application is also related to the following, commonly assigned application, entitled "Apparatus for Controlling Internetwork Communications, "U.S. Patent Application No. 08/926,837. The contents of these Applications are expressly incorporated herein by reference.

Background of the Invention

An automation network includes several nodes, i.e., network devices, connected on a network and controlled from one or more locations. Often times, network designers prefer to use similar, interchangeable devices on a network. Depending on the application of an individual, "standardized," network device, certain functions of the device may not be used.

An automation device such as a programmable logic controller (PLC) generally comprises a computer processing unit, RAM, Flash RAM and a network interface. The application program for controlling the PLC is stored in the Flash Ram, typically consuming 256-512K of Flash RAM. The application code is transmitted to RAM at boot up of the automation device. Depending on the

desired functionality of the automation device, various portions of the application code may not be used. For instance, an all-purpose or "universal" application program can be implemented wherein a standard executive code and user code for the control system exists within the application program for any desired network function. Due to the universality of the application code, the application code can be quite large. Some of the PLCs integrated with the network will not utilize all of the functionality provided within the standardized application program.

Transferring and executing a large application program will affect the overall efficiency of the control system. The unnecessary use of storage space on the system, along with the additional time involved in transferring larger program codes, contributes to the inefficiency of the control system.

The present invention is provided to solve these and other problems.

Summary of the Invention

The present invention is directed to a control system comprising an automation device operably connected to a network. A network device is operably connected to the network and comprises an at least one predetermined application program for controlling the automation device. The application program is selected in response to a message requesting the application program that is sent by the automation device. The application program includes an executive code and a user code. Alternatively, the application program can be dynamic wherein the executive and user codes are selected in response to the message requesting the application program and/or the selected executive and user codes.

Another embodiment of the present invention is directed to a method of operating a control system on a network. An application program is stored on a network device operably connected to the network. A message requesting the application program is originated by the automation device. An application program is selected in response to the message requesting the application program. The selected application program is transmitted and installed on the automation

device. Alternatively, the program application comprises an executive and a user code. The user code is selected in response to the message requesting the application code. The executive code is selected in response to the selected user code. The selected user and executive codes are transmitted to the automation device for execution.

Other features and advantages of the invention, which are believed to be novel and nonobvious, will be apparent from the following specification taken in conjunction with the accompanying drawings in which there is shown a preferred embodiment of the invention. Reference is made to the claims for interpreting the full scope of the invention which is not necessarily represented by such embodiment.

Brief Description of the Drawings

FIGURE 1 is an illustration of a block diagram representing the present invention;

FIGURE 2 shows a block diagram of the present invention illustrating the relationship between an automation device and a network device for storing an application program to be executed on the automation device;

FIGURE 3 shows a block diagram of another embodiment of the present invention; and,

FIGURE 4 shows a block diagram of another embodiment of the present invention.

Detailed Description of the Preferred Embodiment

While this invention is susceptible of embodiment in many different forms, there is shown in the drawings and will herein be described in detail preferred embodiments of the invention with the understanding that the present disclosure is to be considered as an exemplification of the principles of the invention and is not intended to limit the broad aspect of the invention to the embodiments illustrated.

While this invention is susceptible of embodiments in many different forms, there is shown in the drawings and will herein be described in detail preferred embodiments of the invention with the understanding that the present disclosure is to be considered as an exemplification of the principles of the invention and is not intended to limit the broad aspect of the invention to the embodiments illustrated.

A control system shown in FIGURE 1 includes an automation device 10 operably connected to a network 12. The automation device 10, preferably a programmable logic controller (PLC), can be operably connected to other PLCs 10 or input/output (IO) devices 16. The PLC 10 controls and monitors the IO devices 16. Depending on the desired application of PLC 10, the PLC can comprise different hardware and software code.

Other network devices 14, i.e., network personal computer, computer, input/output (IO) module 16, printer, etc., can also be operably connected to the network 12. A network device 14, preferably a server, stores one or more predetermined application programs 20 for use with the automation device 10. The application program 20 is selected in response to a message sent by the automation device 10 requesting the application program. Storing an array of application programs 20 within the network device 14 eliminates the need for the automation device 10 to store its own application programs.

An application program 20 comprises an executive code and a user code for the PLC 10, along with a boot up code. The application program 20 can be stored, created and edited using the network device 14 without requiring the resources of the PLC 10. In addition, a standard or universal application program 20 can be "customized" for a particular function or automation device 10. Thus, depending on the application program 20 required by the automation device 10, the network device 14 can provide the automation device 10 with an application program code that is specifically directed to the desired functionality. The request is generated

by the PLC 10 incorporating a dynamic host configuration (DHCP) or bootstrap (BOOTP) protocol.

Further customization of the application program 20 includes tailoring the executive program of the application program to meet the minimum criteria to effectively execute the application program 20. For example, a single, common, generic application program can reside in the server 14. Subject to the message request sent by the PLC 10 requesting the application program, unutilized sections of the code can be eliminated and parsed out from the generic application program prior to transmitting the selected application program to the PLC. In response to the message request for the application program, the server 14 selects a user code and an executive code. The user code can be selected in response to the message request for the application program. The executive program code can be selected in response to the user code selected and/or the message requesting the application program. Alternatively, several specific, predetermined application codes capable of interacting with any PLC 10 on the network can reside on the network device 14.

The "customized" executive and application program 20 codes improve the efficiency of the network 12 by decreasing the need for storage space on the automation device 10 and allowing for faster transfers of the application program 20 throughout the network 12. In addition, the need for Flash RAM on the automation device 10 to store the application program is significantly reduced. The PLC's Flash RAM will contain the minimum amount of code for downloading the executive and user codes from the network device 14. The application program code 20 for the PLC 10 is stored in the network device 14 and downloaded to the automation device 10 at boot time.

Although the preferred network 12 implementation is Ethernet, other network implementations can also be used such as Internet, Profibus, ControlNet and Modbus+. An application program 20 for controlling an automation device 10 is

stored on a network device 14 operably connected to the network 12. The PLC 10 sends out a BOOTP or DHCP request for obtaining an address on the network 12. A message request from the PLC 10 is transmitted to the network device 14, preferably a server, for acquiring the application program 20. The applicable application program 20 is selected and transmitted from the network device 14 to the PLC 10 in response to the message request for the application program. The application program 20 is then installed and executed on the PLC 10.

FIGURES 2-5 show block diagrams of the present invention illustrating the relationship between an automation device 10 and a network device 14, i.e., server, for storing an application program 20 to be executed on the automation device 10. The server 14 includes a network interface 22 having a unique network address 24 and an application program 20. The server 14 acts as a hypertext transfer protocol (HTTP) interpreter which uses a network protocol, i.e., Transmission Control Protocol (TCP) in conjunction with an Internet Protocol, through a Transmission Control Protocol/Internet Protocol (TCP/IP) stack to interact with the network interface 22 and the application program 20. This enables the transfer of the application program 20 to the PLC 10 through the network 12.

The application program 20 provides an operating program, i.e., executive and user codes; to the PLC 10. The executive code comprises a real time operating system 28, language support 30 and communication support 32. The user code 34 includes ladder logic or IEC 1131 code. The PLC 10 operating program can be stored, created or edited remotely from the PLC 10 and then transmitted to the PLC for use in the control system when desired. The TCP/IP stack enables data transfers over the network as by the IP protocol. The server 14 includes a program package 26 for editing and creating application programs 20. A user can access the program package 26 via a web page. The web page will display a home page which may contain text, some type of multimedia offerings such as graphic

images, video, or audio, and hypertext links to other documents. A user using a browser can view the application program 20 via the web page and edit or create application programs 20 for use on the control system. The browser functions as a remote human-machine interface (HMI) with the network device 14 and the PLC's operating program 20.

It is understood by those skilled in the art that numerous changes and deviations in the form and detail thereof may be made without departing from the spirit and scope of the present invention. For example, the control system can incorporate a wireless network, or a network with a plurality of gateways and bridges. Similarly, the network device can be modified to include more components or to reduce the number of components. However, these variations do not depart from the scope of the present invention wherein network addressing is based, partly or completely, on the physical site location of the devices in the network.

Thus, the present invention has been described with respect to the preferred embodiments thereof. While specific embodiments have been illustrated and described, numerous modifications come to mind without significantly departing from the spirit of the invention and the scope of protection is only limited by the scope of the accompanying claims.

CLAIMS

I CLAIM:

1. A control system, comprising:
an automation device operably connected to a network;
a network device operably connected to the network; and,
5 an application program stored in the network device, wherein the application program controls the automation device, and wherein the application program is selected in response to an application program request message sent from the automation device.
- 10 2. The control system of claim 1 wherein the application program comprises an executive code and a user code.
3. The control system of claim 2 wherein the user code is selected in response to the application program request message sent from the automation device and
15 the executive code is selected in response to the user code selected.
4. The control system of claim 1 wherein the automation device is a programmable logic controller.
- 20 5. The control system of claim 1 wherein the network device is a server.
6. The control system of claim 4 wherein the server has a TCP/IP protocol stack.
- 25 7. The control system of claim 1 wherein the network is Internet.

8. The control system of claim 1 wherein the network is Ethernet.

9. The control system of claim 1 wherein the network is Profibus.

5 10. The control system of claim 1 wherein the network is ControlNet.

11. The control system of claim 1 wherein the network is Modbus+.

12. A method of operating a control system on a network comprising the steps
10 of:

providing a network device for storing an application program to be executed
on an automation device;

transmitting a message for requesting the application program from the
network device;

15 selecting the application program in response to the message for requesting the
application program;

transmitting the application program to the automation device; and,
installing the application program on the automation device.

20 13. The method of claim 12 further comprising the step of executing the
application program on the automation device.

14. The method of claim 12 wherein the step of selecting an application
program in response to the request for the application program comprises the steps
25 of:

identifying the message for requesting the application program;

selecting a user application program in response to the message requesting the
application program; and,

selecting an executive program in response to the user application program selected.

15 15. The method of claim 12, wherein the application program further comprises:
 an executive program code for the automation device; and,
 a user program code for the automation device, the user program is selected in response to the message requesting the application program.

10 16. The method of claim 15 wherein the executive program code is customized in response to the message requesting the application program to meet the minimum requirements for executing the application program.

15 17. A network control system, comprising:
 means for operably connecting a network device to the network control system, the network device stores an application program for controlling an automation device;
 means for transmitting a message requesting the application program;
 means for selecting the application program in response to the message
 20 requesting the application program;
 means for transmitting the application program to the automation device; and,
 means for installing the application program.

25 18. The network control system of claim 17 wherein the means for selecting comprises means for customizing the application program to meet the minimum requirements for executing the application program in response to the request for the application program.

19. The network control system of claim 17 wherein the automation device is a controller.

20. The network control system of claim 17 wherein the network device is a
5 server.

21. A method of operating a control system on a network comprising the steps of:

10 providing a network device for storing an application program to be executed on an automation device;
requesting the application program for the automation device;
selecting the application program in response to the request;
transmitting the application program to the automation device; and,
installing the application program on the automation device.

15 22. The method of claim 21 wherein the selecting the application program includes customizing the application program to meet the minimum requirements for executing the application program selected in response to the message requesting the application program.

20 23. The method of claim 22 wherein the customizing the application program comprises:

selecting a user code in response to the message requesting the application
program; and,
25 selecting an executive code in response to the user code selected.

ABSTRACT

A method and apparatus for a control system of an automation network. The control system comprises an automation device operably connected to the network. Also operably connected to the control system is a network device for storing an application program for controlling the automation device. A message request for the application program is transmitted from the automation device to the network device. A customized application program is selected in response to the message request and transmitted to the automation device. The application program is installed in the automation device and executed.

10

15

20

25




FIGURE 1




FIGURE 2




FIGURE 3

(2) The below-named inventor(s) is/are the original, first inventor(s) of the subject matter which is claimed and for which a patent is sought on the invention entitled "SAA-[✓]", Attorney Docket No. SAA-[✓], the specification of which:

☐ was filed on _____ as Application Serial No. _____.

(4) I(We) acknowledge the duty to disclose all information known to me to be material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, § 1.56.

(5) I(We) hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor certificate listed below and have also identified below any foreign application for patent or inventor certificate having a filing date before that of the application on which priority is claimed:

Priority
Claimed

(Number)	(Country)	(Day/Month/Year Filed)	Yes or No
----------	-----------	------------------------	-----------

Priority
Claimed

(Number)	(Country)	(Day/Month/Year Filed)	Yes or No
----------	-----------	------------------------	-----------

(6) I(We) hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I(We) acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a), regarding events which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)	(Filing Date)	(Status)
--------------------------	---------------	----------

_____ (Application Serial No.)	(Filing Date)	(Status)
--------------------------------	---------------	----------

(7) I(We) hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Larry I. Golden, Registration No. 29,068
Michael J. Femal, Registration No. 27,784
David R. Stacey, Registration No. 33,794
Kareem M. Irfan, Registration No. 32,326
Richard J. Graefe, Registration No. 35,165
Larry T. Shrout, Registration No. 35,357

Direct all telephone calls to: Michael J. Femal at 847/925-3452
Address all correspondence to: Larry I. Golden, Square D Company, 1415 South Roselle Road,
Palatine, IL 60067.

(8) I(We) hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are delivered to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Inventor's Full Name: Rainer H. Wischinski
(First) (Initial) (Last)

Inventor's Signature: *R. H. Wischinski*
Date of Execution: 7/17/00

Residence: Street 110 North Road, Sandown, NH 03873, USA
(Include number, street name, city, state, and country)

Citizenship: Germany

Post Office Address: _____
(If different from Residence Address)

006000" 08252960